Screened power & VFD / motor supply cables

37-108VFD 1kV TC-ER

37-108VFD 1 kV TC-ER Symmetrical VFD Cable

1000 V UL 1277 TC-ER flexible tinned-copper VFD feeder cable

UL 1277 Type TC-ER | U0/U 1000 V · 4 kV AC | EMC Screened




Application

37-108VFD 1 kV TC-ER uses flexible tinned copper conductors, 90 °C thermoset XLPE insulation, three symmetrical grounds, and dual EMC screening for 1000 V inverter-driven industrial motors.

Typical uses: Variable frequency drive (VFD) motor bays, Industrial pumps, fans & compressor skids, Process plants, oil & gas & HVAC systems, Heavy manufacturing & plant MCC feeders

Construction





Cross-section, not to scale

1	Conductor	ASTM B172 Class K flexible tinned annealed copper · ASTM B172 Class K / UL 1277
2	Core insulation	1000 V thermoset XLPE (XHHW-2 / RHW-2) · UL 1277 Type TC-ER
3	Core assembly & separator	Concentric cabled assembly with low-friction fleece or polyester binder tape · UL 1277 Type TC-ER
4	EMC metallic screen	100% Al/polyester foil + ≥ 85% tinned copper braid shield · EMC ≥ 85% / 100% foil
5	Outer sheath	Black heavy-duty CPE/PVC sunlight-resistant jacket · IEEE 1202 / FT4 Flame

Technical data

Typical values

Rated voltage U0/U	1000 V	AC test voltage	4 kV AC / 5 min
Conductor class	ASTM B172 Class K tinned Cu	EMC screen	100% Al/polyester foil + ≥ 85% tinned
Insulation resistance	≥ 1,000 MΩ·km at 20 °C	Temp. range (fixed)	-40 °C to +90 °C
Temp. range (flexing)	-25 °C to +90 °C	Short-circuit temp.	+250 °C (5 s)
Min. bending radius	10 × OD (fixed)	Flame retardance	IEEE 1202 / FT4 Flame
Oil & chemical perf.	UL Oil Res I/II	Environmental / EMC	Sunlight & Direct Burial
Outer sheath	Black heavy-duty CPE/PVC		

Sizes

12 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Cores × AWG/kcmil	Outer Ø ≈ mm	Max. R20 Ω/km	Copper index kg/km	Weight ≈ kg/km	Min. bend R 10×D mm
☐ 3×14 AWG + 3×18 AWG	12.3	9.070	114	244	123
☐ 3×12 AWG + 3×16 AWG	13.3	5.710	164	325	133
☐ 3×10 AWG + 3×14 AWG	14.7	3.590	243	451	147
☐ 3×8 AWG + 3×14 AWG	18.1	2.260	338	646	181
☐ 3×6 AWG + 3×12 AWG	20.2	1.420	513	922	202
☐ 3×4 AWG + 3×12 AWG	24.0	0.892	740	1,322	240
☐ 3×2 AWG + 3×10 AWG	28.5	0.561	1,147	1,996	285
☐ 3×1/0 AWG + 3×6 AWG	32.9	0.353	1,926	3,169	329
☐ 3×2/0 AWG + 3×6 AWG	35.5	0.280	2,315	3,782	355
☐ 3×4/0 AWG + 3×4 AWG	42.4	0.176	3,643	5,832	424
☐ 3×350 kcmil + 3×2 AWG	51.9	0.107	5,935	9,348	519
☐ 3×500 kcmil + 3×2 AWG	59.4	0.075	8,044	12,590	594

- Max. conductor DC resistance R20 at 20 °C per ASTM B172 / B8 (tinned copper).
- Minimum bending radius calculated at 10 × nominal outer diameter (OD). Custom core counts and lengths available on request.

Standards and approvals

- UL 1277 Type TC-ER
- UL 2277 Type WTTC
- ICEA S-95-658
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/37-108vfd-1kv-tc-er-symmetrical-vfd-cable

Typical values for this cable type, based on UL 1277 Type TC-ER · UL 2277 Type WTTC · ICEA S-95-658. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.