Submersible pump cable

510 P

450/750 V AD8 PUR Aquaculture Pump Cable

Submersible pump cable

Submersible pump cable **Order-specific design**




Application

Power connection for submerged pumps and water-handling equipment. Select insulation, sheath and cable entry for the actual liquid and installation.

Typical uses: Water and wastewater, Agriculture, Industrial pumping

Construction





Cross-section, not to scale

1	Conductor	Tinned copper
2	Insulation	Polymer insulation
3	Outer sheath	Polyurethane (PUR)

Technical data

Typical values

Rated voltage	450/750 V	Service profile	Fixed installation with installation flexing
Water exposure	Specify depth, pressure and water chemistry	Chemical compatibility	Verify against the actual fluid and temperature
Standards	Order-specific design		

Sizes

1 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

	Configuration	Rated voltage	Insulation	Outer sheath	Core arrangement
☐	510 P	450/750 V	Polymer insulation	Polyurethane (PUR)	Core count to order

– This reference row describes a construction, not an orderable size. Provide the required core count and cross-section with the enquiry.

Standards and approvals

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/450-750-v-pur-aquaculture-pump-cable

Typical values for this cable type, based on Order-specific design. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.