Subsea umbilical cable

API 17E

Subsea Production Control Umbilical Cable

Subsea umbilical cable

Subsea umbilical cable | Order-specific design



Application

Combined subsea service connection for power, signals, optical elements or fluid lines. Component mix and mechanical design follow the project configuration.

Typical uses: Oil and gas, Marine and offshore, Condition monitoring

Construction





Cross-section, not to scale

1	Conductor	Tinned copper
2	Insulation	Polymer insulation
3	Hydraulic and signal elements	Application-specific elements
4	Outer sheath	Application-specific polymer

Technical data

Typical values

Service profile	Installation-specific duty	**Water exposure**	Specify depth, pressure and water chemistry
Chemical compatibility	Verify against the actual fluid and temperature	**Standards**	API 17E

Sizes

1 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

	Configuration	Rated voltage	Insulation	Outer sheath	Core arrangement
☐	**API 17E**	–	**Polymer insulation**	**Application-specific polymer**	**Power and signal elements**

– This reference row describes a construction, not an orderable size. Provide the required core count and cross-section with the enquiry.

Standards and approvals

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/api-17e-subsea-production-control-umbilical

Typical values for this cable type, based on API 17E. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.