BT CW1308 CW1308

CW1308

PVC-Insulated Multipair Internal Telephone & Voice

BT CW1308 / BS 6746 · 150 V · −15…+70 °C industrial CW1308 construction

BT CW1308 / BS 6746 | 150 V | −15…+70 °C




Application

CW1308 PVC-Insulated Multipair Internal Telephone & Voice Interconnect Cable (CW1308) engineered to BT CW1308 / BS 6746 for 150 V service across −15…+70 °C, featuring stranded copper conductor and pvc outer sheath with minimum bending radius 6 × OD.

Typical uses: Commercial & Residential Building Distribution, Data Centers & Public Infrastructure, Fire-Safe Evacuation & Riser Shafts, Industrial Plant Balance-of-Plant Wiring

Construction





Cross-section, not to scale

1	Stranded copper conductor	BT CW1308 / BS 6746
2	PVC core insulation	BT CW1308 / BS 6746
3	PETP separator	BT CW1308 / BS 6746
4	PVC outer sheath	BT CW1308 / BS 6746

Technical data

Typical values

Rated voltage / duty	150 V (BT CW1308 / BS 6746)	Conductor construction	Stranded copper conductor — High-conductivity copper conductor per BT CW1308 / BS 6746
Primary insulation / dielectric	PVC core insulation — Extruded PVC dielectric (individual core / group layer)	Continuous operating temperature	−15…+70 °C per BT CW1308 / BS 6746
Short-circuit / peak thermal limit	+160 °C to +250 °C (5 s adiabatic limit depending on dielectric class)	Minimum installation temperature	−5 °C (thermoplastic) / −25 °C (cross-linked or elastomer) / −40 °C (metallic)
Outer protection / covering	PVC outer sheath — Extruded PVC outer sheath protective layer (continuous layer)	Minimum bending radius	6 × OD (installed / static routing)
Layer count & geometry	4 concentric/structural layers verified by cross-section inspection	Environmental & chemical durability	Engineered for industrial service in accordance with BT CW1308 / BS 6746
RoHS & REACH compliance	RoHS 2 (2011/65/EU + 2015/863) & REACH SVHC compliant	Standards	BT CW1308 / BS 6746

Sizes

12 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Order designation	Configuration	Outer Ø ≈ mm	Weight ≈ kg/km	Min. bend R fixed mm
CW1308 Standard Construction Schedule (150 V · −15…+70 °C) 12 sizes				
☐ CW1308 1×2×0.5	1×2×0.5 mm²	6.4	58	52
☐ CW1308 2×2×0.5	2×2×0.5 mm²	9.2	112	74
☐ CW1308 4×2×0.5	4×2×0.5 mm²	11.4	176	92
☐ CW1308 8×2×0.5	8×2×0.5 mm²	14.8	295	118
☐ CW1308 12×2×0.5	12×2×0.5 mm²	17.6	420	141
☐ CW1308 1×2×1.0	1×2×1.0 mm²	7.6	86	61
☐ CW1308 2×2×1.0	2×2×1.0 mm²	11.0	168	88
☐ CW1308 4×2×1.0	4×2×1.0 mm²	13.5	264	108
☐ CW1308 8×2×1.0	8×2×1.0 mm²	17.9	465	143
☐ CW1308 1×2×1.5	1×2×1.5 mm²	8.5	114	68
☐ CW1308 4×2×1.5	4×2×1.5 mm²	15.2	348	122
☐ CW1308 12×2×1.5	12×2×1.5 mm²	23.4	860	187

– Additional pair/triad/quad counts (up to 48 pairs) and blue Ex-i intrinsically safe outer sheaths available per BT CW1308 / BS 6746.

Electrical parameters by conductor cross-section

5 sizes

Conductor size	Max. DC R_{20} Ω/km	Mutual cap. ≈ nF/km	Inductance ≈ mH/km
0.50 mm² (7/0.30 mm · AWG 20)	39.00	115	0.65
0.75 mm² (7/0.37 mm · AWG 18)	26.00	120	0.62
1.00 mm² (7/0.43 mm · AWG 17)	19.50	125	0.60
1.50 mm² (7/0.53 mm · AWG 16)	13.30	135	0.58
2.50 mm² (7/0.67 mm · AWG 14)	7.98	145	0.55

– L/R ratio ≤ 25 µH/Ω (0.5–1.0 mm²) and ≤ 40 µH/Ω (1.5 mm²) for intrinsically safe Ex-i circuits.

Standards and approvals

- BT CW1308 Compliant
- EN 10204 3.1 Routine Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/cw1308-pvc-multipair-internal-telephone-interconnect-cable

Typical values for this cable type, based on BT CW1308 / BS 6746. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.