halogen-free shipboard cable

HF-DPYC & HF-DPYCY / HF-SPYC 0.6/1 KV (JIS C 3410)

HF-DPYC & HF-DPYCY / HF-SPYC 0.6/1 kV JIS C 3410 Halogen-Free Shipboar

JIS C 3410 / IEC 60092-353 · 0.6/1 kV · Halogen-free shipboard cable



JIS C 3410 / IEC 60092-353 | 0.6/1 kV (-40 to +90 °C) | SHF1 Zero-Halogen Outer Sheath (HF-.

Application

HF-DPYC, HF-DPYCY & HF-SPYC 0.6/1 kV (JIS C 3410) Halogen-Free Flame-Retardant EPR/XLPE-Insulated Braided-Armoured SHF1 Shipboard Single & Two-Core Power Cable (JIS C 3410 / IEC 60092-353, 0.6/1 kV, -40 to +90 °C).

Typical uses: Passenger Vessels, Ferries & Yachts, Merchant Marine Engine & Cargo Spaces, Offshore Living Quarters & Utility Modules, Shipyard Newbuild & Retrofit Electrical Outfitting

Construction





Cross-section, not to scale

1. Tinned Stranded Copper (2×16 mm²)
2. 90 °C Halogen-Free EPR / XLPE Insulation
3. Halogen-Free Filler & Bedding
4. Galvanized Steel Wire Braid (C)
5. SHF1 Zero-Halogen Outer Sheath (HF-...Y)

Technical data

Typical values

Rated voltage / transmission duty	0.6/1 kV (JIS C 3410:2018 & IEC 60092-353 / IEC 60332-3-22 Cat. A)	**Core / conductor construction**	Tinned Stranded Copper (2×16 mm²) — JIS C 3410 annealed tinned stranded copper conductors
Primary dielectric / buffering	90 °C Halogen-Free EPR / XLPE Insulation — Two-core Black and White halogen-free cross-linked dielectric	**Continuous operating temperature**	−40…+90 °C (shipboard & offshore duty)
Short-circuit / peak thermal rating	Verified thermal stability per JIS C 3410:2018 & IEC 60092-353 / IEC 60332-3-22 Cat. A	**Storage & transport temperature**	−40…+80 °C on export wooden/steel drum
Outer protection / armouring	SHF1 Zero-Halogen Outer Sheath (HF-…Y) — Low-smoke zero-halogen polyolefin jacket certified by ClassNK & KR	**Minimum bending radius**	6 × OD
Armour, screen & mechanical duty	Galvanized Steel Wire Braid (C) — Braided galvanized steel wire armour (copper alloy on single-core HF-SPYC)	**Flame, fire & smoke performance**	Qualified for marine flame-retardance and low-smoke zero-halogen / fire safety per JIS C 3410:2018 & IEC 60092-353 / IEC 60332-3-22 Cat. A
Oil, drilling mud & seawater resistance	Resistant to marine fuel/lube oils, salt mist and offshore fluids per JIS C 3410:2018 & IEC 60092-353 / IEC 60332-3-22 Cat. A	**RoHS & REACH compliance**	RoHS 2 (2011/65/EU + 2015/863) & REACH SVHC compliant
Standards	JIS C 3410:2018 & IEC 60092-353 / IEC 60332-3-22 Cat. A		

Sizes

3 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Order designation	Configuration	Core / stranding	Outer Ø ≈ mm	Net weight ≈ kg/km	Tensile rating kN ≈	Min. bend R mm
HF-DPYC & HF-DPYCY / HF-SPYC 0.6/1 KV (JIS C 3410) Construction Schedule (−40…+90 °C) 3 sizes						
☐ **HF-DPYC 3×16+1G16 mm²**	**3 × 16 + 1G16 mm² (4G16)**	**IEC 60228 Class 2/5 Cu/SnCu**	**22.4**	**920**	**3.8**	**135**
☐ **HF-DPYC 3×35+1G16 mm²**	**3 × 35 + 1G16 mm² (4G35)**	**IEC 60228 Class 2/5 Cu/SnCu**	**28.8**	**1,690**	**7.4**	**175**
☐ **HF-DPYC 3×70+1G35 mm²**	**3 × 70 + 1G35 mm² (4G70)**	**IEC 60228 Class 2/5 Cu/SnCu**	**38.2**	**3,260**	**14.8**	**230**

– Custom core cross-sections, pair/fibre counts, armour grades and factory drum lengths available per JIS C 3410:2018 & IEC 60092-353 / IEC 60332-3-22 Cat. A.

Electrical, optical & thermal parameters

3 sizes

Configuration	Max. DC R_{20} / Atten. Ω/km or dB/km	Rating / Impedance	Operating temp.
3 × 16 + 1G16 mm² (4G16)	**1.15**	**0.6/1 kV (98 A)**	**−40…+90 °C**
3 × 35 + 1G16 mm² (4G35)	**0.52**	**0.6/1 kV (158 A)**	**−40…+90 °C**
3 × 70 + 1G35 mm² (4G70)	**0.27**	**0.6/1 kV (245 A)**	**−40…+90 °C**

– Every production length undergoes routine conductor DC resistance, high-voltage dielectric or OTDR continuity and dimensional verification.

Standards and approvals

- JIS C 3410 / IEC 60092-353 Compliant
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/hf-dpyc-hf-dpycy-hf-spyc-0-6-1-kv-jis-c-3410

Typical values for this cable type, based on JIS C 3410:2018 & IEC 60092-353 / IEC 60332-3-22 Cat. A. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.