submarine & offshore armoured optical cable

HYJQY33 Submarine FO

HYJQY33 12–144F G.652D / G.655 Unrepeatered Steel-Armoured PE-Sheathed

ITU-T G.972 / HYJQY33 · Optical · Submarine & offshore armoured optical cable




ITU-T G.972 / HYJQY33 | Optical (-20 to +70 °C) | Polyethylene (PE) Outer Sheath (HYJQ

Application

HYJQY33 12–144F G.652D / G.655 Unrepeatered Steel-Armoured PE-Sheathed Submarine Optical Cable (ITU-T G.972 / HYJQY33) engineered for Optical service across -20 to +70 °C (min. bend radius 20 × OD).

Typical uses: Submarine Telecom & Cabled Ocean Observatories, Island, Coastal & Inter-Platform Subsea Optical Links, Offshore Platform & FPSO Fire-Safe Optical Backbones, Tactical Marine & Harsh-Environment Optical Deployment

Construction





Cross-section, not to scale

1. Stainless-Steel Loose Tube (12–144×SMF)
2. Polyethylene (PE) Inner Sheath
3. Galvanized Steel Wire Armour
4. Polyethylene (PE) Outer Sheath (HYJQY33)

Technical data

Typical values

Rated voltage / transmission duty	Optical (ITU-T G.972 / G.973 HYJQY33 Unrepeatered Steel-Armoured Submarine Optical Specification)	**Core / conductor construction**	Stainless-Steel Loose Tube (12–144×SMF) — Gel-filled stainless-steel tube housing G.652 / G.654 fibers
Primary dielectric / buffering	Polyethylene (PE) Inner Sheath — Extruded PE inner bedding isolating optical tube from armour	**Continuous operating temperature**	−20…+70 °C (subsea & offshore duty)
Hydrostatic & thermal stability	Verified thermal and hydrostatic stability per ITU-T G.972 / G.973 HYJQY33 Unrepeatered Steel-Armoured Submarine Optical Specification	**Storage & transport temperature**	−40…+80 °C on export wooden/steel winch reel
Outer protection / armouring	Polyethylene (PE) Outer Sheath (HYJQY33) — Extruded black high-density polyethylene outer jacket	**Minimum bending radius**	20 × OD
Armour, strength member & mechanical duty	Galvanized Steel Wire Armour — High-tensile galvanized steel wire armour layer	**Seawater, hydrostatic & hydrolysis resistance**	Engineered for continuous seawater immersion, pressure cycling and hydrolysis resistance per ITU-T G.972 / G.973 HYJQY33 Unrepeatered Steel-Armoured Submarine Optical Specification
Oil, drilling mud & abrasion resistance	Resistant to marine hydraulic oils, salt mist, winch sheave wear and seabed abrasion per ITU-T G.972 / G.973 HYJQY33 Unrepeatered Steel-Armoured Submarine Optical Specification	**RoHS & REACH compliance**	RoHS 2 (2011/65/EU + 2015/863) & REACH SVHC compliant
Standards	ITU-T G.972 / G.973 HYJQY33 Unrepeatered Steel-Armoured Submarine Optical Specification		

Sizes

3 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Order designation	Configuration	Core / stranding	Outer Ø ≈ mm	Net weight ≈ kg/km	Breaking / tensile kN ≈	Min. bend R mm
HYJQY33 Submarine FO Construction Schedule (−20…+70 °C) 3 sizes						
☐ HYJQY33 Submarine FO 4–12F EOM/Sub	4–12 × ITU-T G.652D / G.654E SM (+ Power)	Laser-welded SS FIMT + Steel/Aramid Armour	8.2	260	48.0	125
☐ HYJQY33 Submarine FO 24–48F EOM/Sub	24–48 × ITU-T G.652D / G.654E SM (+ Power)	Laser-welded SS FIMT + Contra-Helical Steel	17.5	680	120.0	260
☐ HYJQY33 Submarine FO 96–192F Trunk	96–192 × ITU-T G.654E / G.652D Submarine	SS Tube + Steel Vault + Cu Tube + DA Armour	28.0	1,650	300.0	420

– Custom core cross-sections, pair/fibre counts, armour breaking loads and continuous winch/seabed lengths available per ITU-T G.972 / G.973 HYJQY33 Unrepeatered Steel-Armoured Submarine Optical Specification.

Electrical, optical & thermal parameters

3 sizes

Configuration	Max. DC R_{20} / Atten. Ω/km or dB/km	Rating / Impedance	Operating temp.
4–12 × ITU-T G.652D / G.654E SM (+ Power)	0.35	≤0.35 dB/km @ 1310 nm	−20…+70 °C
24–48 × ITU-T G.652D / G.654E SM (+ Power)	0.21	≤0.21 dB/km @ 1550 nm	−20…+70 °C
96–192 × ITU-T G.654E / G.652D Submarine	0.18	≤0.18 dB/km @ 1550 nm	−20…+70 °C

– Every production length undergoes routine conductor DC resistance, high-voltage dielectric or OTDR continuity and dimensional verification.

Standards and approvals

- ITU-T G.972 / HYJQY33 Compliant
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/hyjqy33-unrepeatered-subsea-optical-cable

Typical values for this cable type, based on ITU-T G.972 / G.973 HYJQY33 Unrepeatered Steel-Armoured Submarine Optical Specification. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.