Power & distribution cables

LXHI1AE / LXHIAE / LXHIAV 3.6/6kV–18/30kV

DMA-C33-250

IEC 60502-2 / DMA-C33-250 · 3.6/6–18/30 kV · -25°C to +90°C · Min. bend 15 × OD



IEC 60502-2 / DMA-C33-250 | 3.6/6–18/30 kV

Application

LXHI1AE / LXHIAE / LXHIAV 3.6/6kV–18/30kV DMA-C33-250 manufactured to IEC 60502-2 / DMA-C33-250, rated 3.6/6 kV / 6/10 kV / 8.7/15 kV / 12/20 kV / 18/30 kV and -25°C to +90°C with a 15 × OD minimum bending radius for renewable energy installations.

Typical uses: Power distribution & utility networks, Railways, tunnels & public infrastructure, Process instrumentation & oil/gas skids, Industrial automation & control cabinets, Renewable energy, marine & heavy industry

Construction





Cross-section, not to scale

1	Conductor	1×95 mm² Class 2 Stranded Al
2	Insulation & Core Identification	Portuguese LXHI1AE XLPE dielectric (95 mm² Class 2 Stranded Aluminium)
3	Screen / Bedding / Armour Layer	Helical copper tape metallic screen (HI) + Extruded PE/PVC inner separation sheath + Double helically applied aluminium tape armour (1A)
4	Outer Protective Sheath	Black Polyethylene (PE Type ST7) outer sheath (OD 31.0 mm)

Technical data

Typical values

Nominal / reference voltage	3.6/6 kV / 6/10 kV / 8.7/15 kV / 12/20 kV / 18/30 kV	Conductor & core insulation	1×95 mm² Class 2 Stranded Al · Portuguese LXHI1AE XLPE dielectric (95 mm² Class 2 Stranded Aluminium)
Routine dielectric / continuity test	100% factory drum spark & continuity verified	Operating temperature range	-25°C to +90°C
Short-circuit / peak thermal limit	+160 °C to +250 °C (5 s conductor thermal limit)	Flame & fire performance	IEC 60502-2 / DMA-C33-250
Minimum bending radius	15 × OD	Screening / armour architecture	Helical copper tape metallic screen (HI) + Extruded PE/PVC inner separation sheath + Double helically applied aluminium tape armour (1A)
Outer sheath material & colour	Black Polyethylene (PE Type ST7) outer sheath (OD 31.0 mm)	Standards	IEC 60502-2 / DMA-C33-250

Sizes

3 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Part designation	Configuration	Conductor & shield	Insulation / wall	Outer sheath	Outer diameter mm	Min. bend radius mm	Max. conductor resistance @ 20 °C Ω/km	Conductor weight kg/km	Cable weight kg/km	Key electrical / optical rating
LXHI1AE / LXHIAE / LXHIAV 3.6/6kV–18/30kV 3 sizes										
☐ LXHI1AE / LXHIAE / LXHIAV 3.6/6kV–18/30kV (1×95 mm²)	1×95 mm²	Class 2 Compacted Stranded Aluminium	Portuguese LXHI1AE XLPE dielectric	Outdoor PE	31.0	465	0.30	602.7	1,586	188 A
☐ LXHI1AE / LXHIAE / LXHIAV 3.6/6kV–18/30kV (1×120 mm²)	1×120 mm²	Class 2 Compacted Stranded Aluminium	Portuguese LXHI1AE XLPE dielectric	Outdoor PE	36.6	549	0.23	839.0	2,208	218 A
☐ LXHI1AE / LXHIAE / LXHIAV 3.6/6kV–18/30kV (1×150 mm²)	1×150 mm²	Class 2 Compacted Stranded Aluminium	Portuguese LXHI1AE XLPE dielectric	Outdoor PE	42.8	642	0.19	1,147.6	3,020	250 A

– Dimensions and weights are nominal manufacturing targets subject to standard production tolerances.

Standards and approvals

- ✓ IEC 60502-2 / DMA-C33-250 Compliant
- ✓ EN 10204 3.1 Factory Test Certificate
- ✓ CE, UKCA, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone **+86 185 9591 3361**

Email **info@tebaoflex.com**

Web **tebaoflex.com/cables/lxhi1ae-lxhiae-lxhiav-3-6-6kv-18-30kv-dma-c33-250**

Typical values for this cable type, based on Reference specification per IEC 60502-2 / DMA-C33-250 (LXHI1AE / LXHIAE / LXHIAV 3.6/6kV–18/30kV). Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.