submersible aquaculture, pump & marine rubber cable

P7370-SP 1000V Flat XLPE

P7370-SP 1000V Heavy Duty XLPE Flat Submersible Cable

IEC 60502-1 / AS/NZS 5000 · 1,000 V · Submersible aquaculture, pump & marine rubber cable



IEC 60502-1 / AS/NZS 5000 | 1,000 V (-40 to +90 °C) | Subsea / Marine Outer Protective She

Application

P7370-SP 1000V Heavy Duty XLPE Flat Submersible Cable featuring flexible stranded copper conductors (3 cores) and subsea / marine outer protective sheath (IEC 60502-1 / AS/NZS 5000, 1,000 V, -40 to +90 °C, min. bend radius 6 × OD).

Typical uses: Offshore & Coastal Aquaculture Cage Power Distribution, Submersible Aerators, Blowers & Clean-Water Well Pumps, WRAS / KTW Hatchery & Potable Water Pumping Systems, Submersible Pool, Reservoir & Tank Cleaning Robots

Construction





Cross-section, not to scale

1. Flexible Stranded Copper Conductors (3 C
2. Cross-Linked Polyethylene (XLPE) Core In
3. Water-Blocking Elastomeric Bedding Profi
4. Subsea / Marine Outer Protective Sheath

Technical data

Typical values

Rated voltage / operating system	1,000 V (IEC 60502-1 & AS/NZS 5000.1 Heavy-Duty XLPE Flat Submersible Pump Specification)	**Core / conductor construction**	Flexible Stranded Copper Conductors (3 Cores) — IEC 60228 Class 5 finely stranded annealed copper phase conductors
Primary dielectric / optical buffer	Cross-Linked Polyethylene (XLPE) Core Insulation — High-dielectric water-resistant thermoset XLPE insulation laid parallel	**Continuous operating temperature**	−40…+90 °C (submerged seawater & topside deck service)
Hydrostatic & thermal cycling endurance	Verified cold-bend and wet dielectric stability across −40…+90 °C per IEC 60502-1 & AS/NZS 5000.1 Heavy-Duty XLPE Flat Submersible Pump Specification	**Storage & transport temperature**	−40…+80 °C on export wooden/steel cable drum
Outer jacket / sheath protection	Subsea / Marine Outer Protective Sheath — Heavy-duty abrasion- and hydrostatic-pressure-resistant flat outer jacket	**Minimum bending radius**	6 × OD
Reinforcement / screen / bedding layer	Water-Blocking Elastomeric Bedding Profile — Extruded flat moisture-barrier bedding locking parallel cores in place	**Seawater, hydrolysis & oil resistance**	Resistant to permanent seawater immersion, hydrolysis, hydraulic oil and bio-fouling per IEC 60502-1 & AS/NZS 5000.1 Heavy-Duty XLPE Flat Submersible Pump Specification
Hydrostatic pressure & water blocking	Radial and longitudinal water-blocking integrity verified per IEC 60502-1 & AS/NZS 5000.1 Heavy-Duty XLPE Flat Submersible Pump Specification	**RoHS & REACH compliance**	RoHS 2 (2011/65/EU + 2015/863) & REACH SVHC compliant
Standards	IEC 60502-1 & AS/NZS 5000.1 Heavy-Duty XLPE Flat Submersible Pump Specification		

Sizes

3 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Order designation	Configuration	Core / stranding	Outer Ø ≈ mm	Net weight ≈ kg/km	Max. pulling kN ≈	Min. bend R mm
P7370-SP 1000V Flat XLPE Construction Schedule (−40…+90 °C) 3 sizes						
☐ **P7370-SP 1000V Flat XLPE 4G4.0 mm²**	**4G4.0 mm² (3×4.0 + 1G4.0 / 12 AWG)**	**IEC 60228 Class 5 Cu/SnCu**	**14.2**	**340**	**3.2**	**85**
☐ **P7370-SP 1000V Flat XLPE 4G16 mm²**	**4G16 mm² (3×16 + 1G16 / 6 AWG)**	**IEC 60228 Class 5 Cu/SnCu**	**21.4**	**840**	**9.6**	**130**
☐ **P7370-SP 1000V Flat XLPE 3×50+1G25 mm²**	**3 × 50 + 1G25 mm² (or 3×70+1G35)**	**IEC 60228 Class 5 Cu/SnCu**	**32.8**	**2,240**	**26.5**	**195**

– Custom core counts, optical fiber channels, wet-mate terminations and continuous winch lengths available per IEC 60502-1 & AS/NZS 5000.1 Heavy-Duty XLPE Flat Submersible Pump Specification.

Electrical, optical & thermal parameters

3 sizes

Configuration	Max. DC R_{20} Ω/km	Rating / Impedance / Load	Operating temp.
4G4.0 mm² (3×4.0 + 1G4.0 / 12 AWG)	**4.95**	**1,000 V (36 A Submersible)**	**−40…+90 °C**
4G16 mm² (3×16 + 1G16 / 6 AWG)	**1.21**	**1,000 V (98 A Submersible)**	**−40…+90 °C**
3 × 50 + 1G25 mm² (or 3×70+1G35)	**0.39**	**1,000 V (195 A Feeder)**	**−40…+90 °C**

– Every production length undergoes routine conductor DC resistance / OTDR optical attenuation, AC dielectric and dimensional verification.

Standards and approvals

- IEC 60502-1 / AS/NZS 5000 Compliant
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/p7370-sp-1000v-heavy-duty-xlpe-flat-submersible-cable

Typical values for this cable type, based on IEC 60502-1 & AS/NZS 5000.1 Heavy-Duty XLPE Flat Submersible Pump Specification. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.