IEC 61158-2 PB-HYBRID 2×0.34 + 4×1.5 PUR

PB-HYBRID 2×0.34 + 4×1.5 PUR

PROFIBUS Data + Power PUR Drag-Chain Hybrid Bus Cable

IEC 61158-2 / UL AWM 21198 · 300 V · −40…+80 °C industrial PB-HYBRID 2×0.34 + 4×1.5 PUR



IEC 61158-2 / UL AWM 21198 | 300 V | −40…+80 °C


Application

PROFIBUS Data + Power PUR Drag-Chain Hybrid Bus Cable engineered to IEC 61158-2 / UL AWM 21198 for 300 V service across −40…+80 °C, featuring stranded copper conductor and pur outer sheath ral 4001 with minimum bending radius 7.5 × OD.

Typical uses: Automated Assembly & Packaging Lines, CNC Machine Tools & Robotics, PLC/DCS Control & Marshalling Cabinets, Industrial Drives & Motor Manufacturing

Construction





Cross-section, not to scale

1	Stranded copper conductor	IEC 61158-2 / UL AWM 21198
2	TPE core insulation	IEC 61158-2 / UL AWM 21198
3	Signal tinned copper braid	IEC 61158-2 / UL AWM 21198
4	Cellular PE core insulation	IEC 61158-2 / UL AWM 21198
5	PUR outer sheath RAL 4001	IEC 61158-2 / UL AWM 21198

Technical data

Typical values

Rated voltage / duty	300 V (IEC 61158-2 / UL AWM 21198)	**Conductor construction**	Stranded copper conductor — High-conductivity copper conductor per IEC 61158-2 / UL AWM 21198
Primary insulation / dielectric	TPE core insulation — Extruded TPE dielectric (individual core / group layer)	**Continuous operating temperature**	−40…+80 °C per IEC 61158-2 / UL AWM 21198
Short-circuit / peak thermal limit	+160 °C to +250 °C (5 s adiabatic limit depending on dielectric class)	**Minimum installation temperature**	−5 °C (thermoplastic) / −25 °C (cross-linked or elastomer) / −40 °C (metallic)
Outer protection / covering	PUR outer sheath RAL 4001 — Extruded PUR outer sheath RAL 4001 protective layer (continuous layer)	**Minimum bending radius**	7.5 × OD (installed / static routing)
Layer count & geometry	5 concentric/structural layers verified by cross-section inspection	**Environmental & chemical durability**	Engineered for industrial service in accordance with IEC 61158-2 / UL AWM 21198
RoHS & REACH compliance	RoHS 2 (2011/65/EU + 2015/863) & REACH SVHC compliant	**Standards**	IEC 61158-2 / UL AWM 21198

Sizes

12 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Order designation	Configuration	Outer Ø ≈ mm	Weight ≈ kg/km	Min. bend R fixed mm
PB-HYBRID 2×0.34 + 4×1.5 PUR Standard Production Schedule (300 V · −40…+80 °C) 12 sizes				
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 3G1.5**	3 × 1.5 mm²	8.4	105	68
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 4G1.5**	4 × 1.5 mm²	9.2	128	74
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 5G1.5**	5 × 1.5 mm²	10.1	156	81
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 3G2.5**	3 × 2.5 mm²	9.8	148	78
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 4G2.5**	4 × 2.5 mm²	10.8	186	86
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 5G2.5**	5 × 2.5 mm²	11.9	228	95
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 4G4**	4 × 4.0 mm²	12.6	268	101
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 4G6**	4 × 6.0 mm²	14.2	365	114
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 4G10**	4 × 10 mm²	17.5	580	140
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 4G16**	4 × 16 mm²	20.4	845	163
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 4G25**	4 × 25 mm²	24.8	1,290	198
☐ **PB-HYBRID 2×0.34 + 4×1.5 PUR 4G35**	4 × 35 mm²	27.9	1,710	223

– Single-core and multi-core sizes from 0.5 mm² up to 630 mm² (or AWG/kcmil) available per IEC 61158-2 / UL AWM 21198.

Conductor resistance & current-carrying capacity

8 sizes

Cross-section	Max. DC R_{20} Ω/km	Current in air A (30 °C) ≈	Voltage drop mV/A-m
1.5 mm² (AWG 16)	13.30	18	29.0
2.5 mm² (AWG 14)	7.98	26	17.5
4.0 mm² (AWG 12)	4.95	34	10.9
6.0 mm² (AWG 10)	3.30	44	7.3
10 mm² (AWG 8)	1.91	61	4.2
16 mm² (AWG 6)	1.21	82	2.7
25 mm² (AWG 4)	0.78	108	1.7
35 mm² (AWG 2)	0.55	135	1.2

– Current ratings are for 3 loaded conductors at 30 °C ambient in free air/tray per IEC 60364-5-52 / NEC.

Standards and approvals

- IEC 61158-2 Compliant
- EN 10204 3.1 Routine Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/pb-hybrid-2x0-34-4x1-5-pur-profibus-drag-chain-cable

Typical values for this cable type, based on IEC 61158-2 / UL AWM 21198. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.