Industrial heating cable

QTVR

110 °C Process Maintenance Heating Cable

Industrial heating cable

Industrial heating cable **Order-specific design**




Application

Heat tracing for pipes and process equipment. Select supply, heating output, maintain temperature, exposure temperature and circuit protection together.

Typical uses: Oil and gas, Process plants, Marine and offshore

Construction





Cross-section, not to scale

1	Bus conductors	Bus conductors
2	Sensing element	Self-regulating polymer
3	Protective braid	Metallic screen
4	Outer sheath	Fluoropolymer

Technical data

Typical values

Maintain temperature	+110 °C	Service profile	Fixed installation with installation flexing
Water exposure	Specify depth, pressure and water chemistry	Chemical compatibility	Verify against the actual fluid and temperature
Standards	Order-specific design		

Sizes

1 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

	Configuration	Rated voltage	Insulation	Outer sheath	Core arrangement
☐	QTVR	–	Self-regulating polymer	Fluoropolymer	Parallel bus conductors

– This reference row describes a construction, not an orderable size. Provide the required core count and cross-section with the enquiry.

Standards and approvals

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/110-c-process-maintenance-heating-cable

Typical values for this cable type, based on Order-specific design. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.