High-temperature fluoropolymer, silicone & HV wires

SAE AS22759/11

600 V 200 °C PTFE Aerospace Wire

Silver-plated copper extruded PTFE 600 V aircraft airframe wire

SAE AS22759/11 | 600 V · +200 °C | Fluoropolymer HT



Application

SAE AS22759/11 pairs stranded silver-plated copper with extruded PTFE fluoropolymer insulation rated 600 V and 200 °C for commercial and military aircraft avionics, engine accessories, and flight-control looms.

Typical uses: Industrial ovens, kilns & thermal processing, Aerospace avionics, defence & instrumentation, Steelworks, glassworks & foundry equipment, Switchgear cabinets, motors & heating appliances

Construction





Cross-section, not to scale

1	Conductor	ASTM B298 Class K stranded silver-plated annealed copper · ASTM B298 Silver Cu
2	Extruded insulation	Extruded off-white PTFE fluoropolymer aerospace insulation · SAE AS22759/11

Technical data

Typical values

Rated voltage	600 V	**Test voltage**	2.5 kV AC
Conductor	Silver-Plated Cu	**Insulation**	Extruded off-white PTFE fluoropolymer
Impedance / insulation	≥ 1,000 MΩ·km at 20 °C	**Temp. range (fixed)**	-65 °C to +200 °C
Temp. range (flexing)	-55 °C to +200 °C	**Peak / short-circuit**	+220 °C (short-term)
Min. bending radius	6 × OD (fixed)	**Flame / fire rating**	200 °C Aerospace PTFE
Thermal / chemical	FAR 25.869 Flame	**Mechanical / special**	Skydrol & Jet-Fuel Proof
Outer finish	Off-white extruded PTFE fluoropolymer		

Sizes

8 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Conductor AWG	Outer Ø ≈ mm	Max. R20 Ω/km	Metal index kg/km	Weight ≈ kg/km	Min. bend R 6×D mm
☐ 1×28 AWG	0.9	238.00	1	9	5.4
☐ 1×26 AWG	1.0	150.00	1	9	6.0
☐ 1×24 AWG	1.1	94.20	2	11	6.6
☐ 1×22 AWG	1.3	59.40	3	12	7.8
☐ 1×20 AWG	1.5	36.70	5	14	9.0
☐ 1×18 AWG	1.7	23.20	7	17	10.2
☐ 1×16 AWG	2.0	14.70	12	23	12.0
☐ 1×14 AWG	2.4	9.07	19	35	14.0

- Conductor DC resistance R20 at 20 °C per ASTM B298 Silver Cu.
- Minimum bending radius calculated at 6 × nominal outer diameter (OD). Custom core counts and lengths available on request.

Standards and approvals

- SAE AS22759/11
- MIL-W-22759/11
- ASTM B298 Silver Cu
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/sae-as22759-11-600v-200c-ptfe-aerospace-wire

Typical values for this cable type, based on SAE AS22759/11 · MIL-W-22759/11 · ASTM B298 Silver Cu. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.