High-temperature fluoropolymer, silicone & HV wires

SAE AS22759/16

600 V 150 °C ETFE Aerospace Wire

Tinned copper extruded ETFE 600 V lightweight airframe hook-up wire



SAE AS22759/16 | 600 V · +150 °C | Fluoropolymer HT

Application

SAE AS22759/16 combines stranded tinned copper with tough extruded ETFE fluoropolymer insulation rated 600 V and 150 °C for abrasion-prone commercial aircraft wire harnesses and instrumentation panels.

Typical uses: Industrial ovens, kilns & thermal processing, Aerospace avionics, defence & instrumentation, Steelworks, glassworks & foundry equipment, Switchgear cabinets, motors & heating appliances

Construction





Cross-section, not to scale

1	Conductor	ASTM B172 / B33 Class K flexible tinned annealed copper · ASTM B172 / B33
2	Extruded insulation	Extruded white ETFE fluoropolymer insulation · SAE AS22759/16

Technical data

Typical values

Rated voltage	600 V	Test voltage	2.5 kV AC
Conductor	Tinned Cu · Cl.K	Insulation	Extruded white ETFE fluoropolymer insulation
Impedance / insulation	≥ 1,000 MΩ·km at 20 °C	Temp. range (fixed)	-65 °C to +150 °C
Temp. range (flexing)	-55 °C to +150 °C	Peak / short-circuit	+160 °C (5 s)
Min. bending radius	6 × OD (fixed)	Flame / fire rating	150 °C Tough ETFE
Thermal / chemical	High Cut-Through Strength	Mechanical / special	FAR 25.869 Flame
Outer finish	White extruded ETFE fluoropolymer outer		

Sizes

8 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Conductor AWG	Outer Ø ≈ mm	Max. R20 Ω/km	Metal index kg/km	Weight ≈ kg/km	Min. bend R 6×D mm
☐ 1×24 AWG	1.4	94.20	2	11	8.4
☐ 1×22 AWG	1.6	59.40	3	12	9.6
☐ 1×20 AWG	1.8	36.70	5	14	10.8
☐ 1×18 AWG	2.0	23.20	7	17	12.0
☐ 1×16 AWG	2.4	14.70	12	25	14.0
☐ 1×14 AWG	2.8	9.07	19	37	17.0
☐ 1×12 AWG	3.3	5.71	30	57	20.0
☐ 1×10 AWG	3.9	3.59	48	89	23.0

- Conductor DC resistance R20 at 20 °C per ASTM B172 / B33.
- Minimum bending radius calculated at 6 × nominal outer diameter (OD). Custom core counts and lengths available on request.

Standards and approvals

- SAE AS22759/16
- MIL-W-22759/16
- ASTM B33 Tinned Cu
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/sae-as22759-16-600v-150c-etfe-aerospace-wire

Typical values for this cable type, based on SAE AS22759/16 · MIL-W-22759/16 · ASTM B33 Tinned Cu. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.