submarine aquaculture, shore power & shipboard power cable

TERE 24kV Submarine Aquaculture

Power Optic Cable

IEC 60502-2 / HD 620 · 12/20 (24) kV · Submarine aquaculture, shore power & shipboard



IEC 60502-2 / HD 620 | 12/20 (24) kV (-20 to +90 °C) | Double Torque-Balanced Steel Wire Ar


Application

TERE 24kV Submarine Aquaculture Power Optic Cable featuring single-mode / multi-mode optical unit and double torque-balanced steel wire armour (IEC 60502-2 / HD 620, 12/20 (24) kV, -20 to +90 °C, min. bend radius 15 × OD).

Typical uses: Submarine Electro-Optical Marine Ranch & Island Grids, NEK 400-8-820 / NS 9415 Floating Fish Farm Power Distribution, Aquaculture Workboats, Live-Fish Carriers & Offshore Vessels, Port Marina & Fishing Harbour Shore Power Connections

Construction





Cross-section, not to scale

1. Single-Mode / Multi-Mode Optical Unit
2. Power & Control Copper Conductors
3. Double Torque-Balanced Steel Wire Armour

Technical data

Typical values

Rated voltage / operating system	12/20 (24) kV (IEC 60502-2 & HD 620 TERE 24 kV Submarine Aquaculture Power-Optic Standard)
Primary dielectric / optical buffer	Power & Control Copper Conductors — Stranded copper conductors with Cross-linked polyethylene (XLPE) insulation
Hydrostatic & thermal cycling endurance	Verified cold-bend and wet dielectric stability across −20…+90 °C per IEC 60502-2 & HD 620 TERE 24 kV Submarine Aquaculture Power-Optic Standard
Outer jacket / sheath protection	Double Torque-Balanced Steel Wire Armour — Contra-helical high-tensile galvanized steel wire armour
Reinforcement / screen / bedding layer	Power & Control Copper Conductors — Stranded copper conductors with Cross-linked polyethylene (XLPE) insulation
Hydrostatic pressure & water blocking	Radial and longitudinal water-blocking integrity verified per IEC 60502-2 & HD 620 TERE 24 kV Submarine Aquaculture Power-Optic Standard
Standards	IEC 60502-2 & HD 620 TERE 24 kV Submarine Aquaculture Power-Optic Standard
Core / conductor construction	Single-Mode / Multi-Mode Optical Unit — Hermetic stainless-steel tube / tight-buffered optical unit
Continuous operating temperature	−20…+90 °C (submerged seawater & topside deck service)
Storage & transport temperature	−40…+80 °C on export wooden/steel cable drum
Minimum bending radius	15 × OD
Seawater, hydrolysis & oil resistance	Resistant to permanent seawater immersion, hydrolysis, hydraulic oil and bio-fouling per IEC 60502-2 & HD 620 TERE 24 kV Submarine Aquaculture Power-Optic Standard
RoHS & REACH compliance	RoHS 2 (2011/65/EU + 2015/863) & REACH SVHC compliant

Sizes

3 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Order designation	Configuration	Core / stranding	Outer Ø ≈ mm	Net weight ≈ kg/km	Max. pulling kN ≈	Min. bend R mm
TERE 24kV Submarine Aquaculture Construction Schedule (−20…+90 °C) 3 sizes						
☐ TERE 24kV Submarine Aquaculture 3×6 + 4×SM + 2TP	3×6 mm² Power + 4×SM Fiber + 2×2×0.75	SnCu + Gel Tube + Contra-Helical GSWA	20.8	1,280	115.0	250
☐ TERE 24kV Submarine Aquaculture 3×10 + 6×SM + 4T	3×10 mm² Power + 6×SM Fiber + 4×2×0.75	SnCu + SS Tube + Double Steel Armour	25.4	1,890	185.0	305
☐ TERE 24kV Submarine Aquaculture 3×16 + 8×SM/MM	3×16 mm² Power + 8×SM/MM + 3×2×1.0	SnCu + SS Tube + Heavy GSWA Pack	30.2	2,680	260.0	365

– Custom core counts, optical fiber channels, wet-mate terminations and continuous winch lengths available per IEC 60502-2 & HD 620 TERE 24 kV Submarine Aquaculture Power-Optic Standard.

Electrical, optical & thermal parameters

3 sizes

Configuration	Max. DC R_{20} Ω/km	Rating / Impedance / Load	Operating temp.
3×6 mm² Power + 4×SM Fiber + 2×2×0.75	3.30	12/20 (24) kV · 115 kN MBS	−20…+90 °C
3×10 mm² Power + 6×SM Fiber + 4×2×0.75	1.91	12/20 (24) kV · 185 kN MBS	−20…+90 °C
3×16 mm² Power + 8×SM/MM + 3×2×1.0	1.21	12/20 (24) kV · 260 kN MBS	−20…+90 °C

– Every production length undergoes routine conductor DC resistance / OTDR optical attenuation, AC dielectric and dimensional verification.

Standards and approvals

- IEC 60502-2 / HD 620 Compliant
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/tere-24kv-submarine-aquaculture-power-optic-cable

Typical values for this cable type, based on IEC 60502-2 & HD 620 TERE 24 kV Submarine Aquaculture Power-Optic Standard. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.