marine winch, salvage, shore power & crawler reeling cable

TF-Reel Fiber-Power Umbilical

TF-Reel Drum Reeling Fiber & Power Umbilical

DIN VDE 0250-814 / IEC 60794 · 0.6/1 kV (1.8/3 kV) · Marine winch, salvage, shore



DIN VDE 0250-814 / IEC 60794 | 0.6/1 kV (1.8/3 kV) (-40 to +80 °C) | Subsea / Marine Outer Protective She

Application

TF-Reel Drum Reeling Fiber & Power Umbilical featuring single-mode / multi-mode optical unit and subsea / marine outer protective sheath (DIN VDE 0250-814 / IEC 60794, 0.6/1 kV (1.8/3 kV), -40 to +80 °C, min. bend radius 6 × OD).

Typical uses: Marine Salvage, Deck Crane & Oceanographic Winch Drums, High-Voltage & Low-Voltage Port Shore Power (AMP / HVSC) Reels, Seabed Crawler, Amphibious Excavator & Dredge Reeling Systems, Offshore Aquaculture Feed Barge & Net-Handling Winches

Construction





Cross-section, not to scale

1. Single-Mode / Multi-Mode Optical Unit
2. Power & Control Copper Conductors
3. Aramid / LCP Braided Strength Member
4. Subsea / Marine Outer Protective Sheath

Technical data

Typical values

Rated voltage / operating system	0.6/1 kV (1.8/3 kV) (DIN VDE 0250-814 TF-Reel Drum Reeling Fiber & Power Umbilical Specification)	**Core / conductor construction**	Single-Mode / Multi-Mode Optical Unit — Hermetic stainless-steel tube / tight-buffered optical unit
Primary dielectric / optical buffer	Power & Control Copper Conductors — Stranded copper conductors with High-modulus ethylene-propylene rubber (HEPR) insulation	**Continuous operating temperature**	−40…+80 °C (submerged seawater & topside deck service)
Hydrostatic & thermal cycling endurance	Verified cold-bend and wet dielectric stability across −40…+80 °C per DIN VDE 0250-814 TF-Reel Drum Reeling Fiber & Power Umbilical Specification	**Storage & transport temperature**	−40…+80 °C on export wooden/steel cable drum
Outer jacket / sheath protection	Subsea / Marine Outer Protective Sheath — Black hydrolysis- & abrasion-resistant marine Polyurethane (PUR) outer sheath	**Minimum bending radius**	6 × OD
Reinforcement / screen / bedding layer	Aramid / LCP Braided Strength Member — High-tenacity synthetic fiber braid absorbing dynamic tension	**Seawater, hydrolysis & oil resistance**	Resistant to permanent seawater immersion, hydrolysis, hydraulic oil and bio-fouling per DIN VDE 0250-814 TF-Reel Drum Reeling Fiber & Power Umbilical Specification
Hydrostatic pressure & water blocking	Radial and longitudinal water-blocking integrity verified per DIN VDE 0250-814 TF-Reel Drum Reeling Fiber & Power Umbilical Specification	**RoHS & REACH compliance**	RoHS 2 (2011/65/EU + 2015/863) & REACH SVHC compliant
Standards	DIN VDE 0250-814 TF-Reel Drum Reeling Fiber & Power Umbilical Specification		

Sizes

3 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Order designation	Configuration	Core / stranding	Outer Ø ≈ mm	Net weight ≈ kg/km	Max. pulling kN ≈	Min. bend R mm
TF-Reel Fiber-Power Umbilical Construction Schedule (−40…+80 °C) 3 sizes						
☐ **TF-Reel Fiber-Power Umbilical Hybrid 4G2.5+FO**	4G2.5 mm² Power + 4×SM + 2×2×0.5	Class 5 SnCu + Aramid Braid + Subsea PUR	14.6	285	18.0	90
☐ **TF-Reel Fiber-Power Umbilical Hybrid 4G6+FO**	4G6.0 mm² Power + 4×SM/MM + 4×2×0.5	Class 5 SnCu + Aramid Braid + Subsea PUR	19.2	540	32.0	120
☐ **TF-Reel Fiber-Power Umbilical Hybrid 4G16+FO**	4G16 mm² Power + 8×SM/MM + 4×2×0.75	Class 5 SnCu + Heavy Aramid + Subsea PUR	26.5	1,120	55.0	165

– Custom core counts, optical fiber channels, wet-mate terminations and continuous winch lengths available per DIN VDE 0250-814 TF-Reel Drum Reeling Fiber & Power Umbilical Specification.

Electrical, optical & thermal parameters

3 sizes

Configuration	Max. DC R_{20} Ω/km	Rating / Impedance / Load	Operating temp.
4G2.5 mm² Power + 4×SM + 2×2×0.5	7.98	0.6/1 kV (1.8/3 kV) · 18 kN Tensile	−40…+80 °C
4G6.0 mm² Power + 4×SM/MM + 4×2×0.5	3.30	0.6/1 kV (1.8/3 kV) · 32 kN Tensile	−40…+80 °C
4G16 mm² Power + 8×SM/MM + 4×2×0.75	1.21	0.6/1 kV (1.8/3 kV) · 55 kN Tensile	−40…+80 °C

– Every production length undergoes routine conductor DC resistance / OTDR optical attenuation, AC dielectric and dimensional verification.

Standards and approvals

- DIN VDE 0250-814 / IEC 60794 Compliant
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/tf-reel-drum-reeling-fiber-power-umbilical

Typical values for this cable type, based on DIN VDE 0250-814 TF-Reel Drum Reeling Fiber & Power Umbilical Specification. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.