High-temperature fluoropolymer, silicone & HV wires

UL 1213 PTFE Equipment Wire

UL AWM 1213 Thin-Wall PTFE Equipment Hook-Up Wire

UL 758 Style 1213 compact 10-mil extruded PTFE electronics hook-up wire



UL AWM Style 1213 | 600 V · +200 °C | Fluoropolymer HT

Application

UL 1213 PTFE Equipment Wire combines stranded silver-plated copper with a slim 10-mil extruded green PTFE fluoropolymer insulation for solder-proof internal wiring of test equipment, power supplies, and sensors.

Typical uses: Industrial ovens, kilns & thermal processing, Aerospace avionics, defence & instrumentation, Steelworks, glassworks & foundry equipment, Switchgear cabinets, motors & heating appliances

Construction





Cross-section, not to scale

1	**Conductor**	ASTM B298 Class K stranded silver-plated annealed copper · ASTM B298 Silver Cu
2	**Extruded insulation**	Green 10-mil extruded PTFE fluoropolymer insulation · UL AWM Style 1213

Technical data

Typical values

Rated voltage	600 V	**Test voltage**	2 kV AC
Conductor	Silver-Plated Cu	**Insulation**	Green 10-mil extruded PTFE fluoropolymer
Impedance / insulation	≥ 1,000 MΩ·km at 20 °C	**Temp. range (fixed)**	-65 °C to +200 °C
Temp. range (flexing)	-55 °C to +200 °C	**Peak / short-circuit**	+220 °C (short-term)
Min. bending radius	6 × OD (fixed)	**Flame / fire rating**	UL VW-1 Flame
Thermal / chemical	Solder-Iron Proof PTFE	**Mechanical / special**	Low Dielectric Loss
Outer finish	Green 10-mil extruded PTFE fluoropolymer		

Sizes

8 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Conductor AWG	Outer Ø ≈ mm	Max. R20 Ω/km	Metal index kg/km	Weight ≈ kg/km	Min. bend R 6×D mm
☐ 1×28 AWG	0.9	238.00	1	9	5.4
☐ 1×26 AWG	1.0	150.00	1	9	6.0
☐ 1×24 AWG	1.1	94.20	2	11	6.6
☐ 1×22 AWG	1.3	59.40	3	12	7.8
☐ 1×20 AWG	1.5	36.70	5	14	9.0
☐ 1×18 AWG	1.7	23.20	7	17	10.2
☐ 1×16 AWG	2.0	14.70	12	23	12.0
☐ 1×14 AWG	2.4	9.07	19	35	14.0

- Conductor DC resistance R20 at 20 °C per ASTM B298 Silver Cu.
- Minimum bending radius calculated at 6 × nominal outer diameter (OD). Custom core counts and lengths available on request.

Standards and approvals

- UL AWM Style 1213
- UL 758
- MIL-DTL-16878/4 (ref.)
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/ul-1213-105c-ptfe-thin-wall-equipment-wire

Typical values for this cable type, based on UL AWM Style 1213 · UL 758 · MIL-DTL-16878/4 (ref.). Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.