High-temperature fluoropolymer, silicone & HV wires

UL 1726 300V PFA

UL AWM 1726 300 V 250 °C PFA High-Temp Hook-Up Wire

UL 758 Style 1726 300 V 250 °C thin-wall PFA fluoropolymer lead wire

UL AWM Style 1726 | 300 V · +250 °C | Fluoropolymer HT



Application

UL 1726 250 °C 300 V PFA combines nickel-plated copper conductors with smooth 13-mil yellow extruded PFA fluoropolymer insulation for 250 °C heating appliances, thermal fuses, and lab analyzers.

Typical uses: Industrial ovens, kilns & thermal processing, Aerospace avionics, defence & instrumentation, Steelworks, glassworks & foundry equipment, Switchgear cabinets, motors & heating appliances

Construction





Cross-section, not to scale

1	Conductor	ASTM B355 Class K stranded nickel-plated annealed copper · ASTM B355 Nickel Cu
2	Extruded insulation	Yellow 13-mil extruded PFA fluoropolymer insulation (250 °C) · UL AWM Style 1726

Technical data

Typical values

Rated voltage	300 V	Test voltage	2 kV AC
Conductor	Nickel-Plated Cu	Insulation	Yellow 13-mil extruded PFA fluoropolymer
Impedance / insulation	≥ 1,000 MΩ·km at 20 °C	Temp. range (fixed)	-100 °C to +250 °C
Temp. range (flexing)	-65 °C to +250 °C	Peak / short-circuit	+300 °C (short-term)
Min. bending radius	6 × OD (fixed)	Flame / fire rating	UL VW-1 / FT1 Flame
Thermal / chemical	250 °C Continuous PFA	Mechanical / special	Acid & Steam Resistant
Outer finish	Yellow 13-mil extruded PFA fluoropolymer		

Sizes

8 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Conductor AWG	Outer Ø ≈ mm	Max. R20 Ω/km	Metal index kg/km	Weight ≈ kg/km	Min. bend R 6×D mm
☐ 1×28 AWG	0.9	259.42	1	9	5.4
☐ 1×26 AWG	1.0	163.50	1	9	6.0
☐ 1×24 AWG	1.1	102.68	2	11	6.6
☐ 1×22 AWG	1.3	64.75	3	12	7.8
☐ 1×20 AWG	1.5	40.00	5	14	9.0
☐ 1×18 AWG	1.7	25.29	7	17	10.2
☐ 1×16 AWG	2.0	16.02	12	23	12.0
☐ 1×14 AWG	2.4	9.89	19	35	14.0

- Conductor DC resistance R20 at 20 °C per ASTM B355 Nickel Cu.
- Minimum bending radius calculated at 6 × nominal outer diameter (OD). Custom core counts and lengths available on request.

Standards and approvals

- UL AWM Style 1726
- UL 758
- CSA AWM I A/B
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/ul-1726-300v-250c-pfa-high-temp-hook-up-wire

Typical values for this cable type, based on UL AWM Style 1726 · UL 758 · CSA AWM I A/B. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.