submersible aquaculture, pump & marine rubber cable

WRAS/KTW EPDM Pump Cable

WRAS KTW Clean Water EPDM Submersible Pump Cable

BS 6920 WRAS / KTW / EN 50525 · 450/750 V (0.6/1 kV) · Submersible aquaculture, pump &




BS 6920 WRAS / KTW / EN 50525 | 450/750 V (0.6/1 kV) (-40 to +90 °C) | Subsea / Marine Outer Protective She

Application

WRAS KTW Clean Water EPDM Submersible Pump Cable featuring flexible stranded copper conductors (4 cores) and subsea / marine outer protective sheath (BS 6920 WRAS / KTW / EN 50525, 450/750 V (0.6/1 kV), -40 to +90 °C).

Typical uses: Offshore & Coastal Aquaculture Cage Power Distribution, Submersible Aerators, Blowers & Clean-Water Well Pumps, WRAS / KTW Hatchery & Potable Water Pumping Systems, Submersible Pool, Reservoir & Tank Cleaning Robots

Construction





Cross-section, not to scale

1. Flexible Stranded Copper Conductors (4 C
2. Cross-Linked Elastomeric / Polymer Core
3. Water-Blocking Tape & Inner Bedding
4. Subsea / Marine Outer Protective Sheath

Technical data

Typical values

Rated voltage / operating system	450/750 V (0.6/1 kV) (BS 6920 WRAS & KTW Approved EPDM Clean-Water Submersible Pump Standard)
Primary dielectric / optical buffer	Cross-Linked Elastomeric / Polymer Core Insulation — Ethylene-propyiene rubber (epr/epdm) insulation
Hydrostatic & thermal cycling endurance	Verified cold-bend and wet dielectric stability across −40…+90 °C per BS 6920 WRAS & KTW Approved EPDM Clean-Water Submersible Pump Standard
Outer jacket / sheath protection	Subsea / Marine Outer Protective Sheath — Blue clean-water non-toxic EPDM rubber outer sheath (AD8)
Reinforcement / screen / bedding layer	Water-Blocking Tape & Inner Bedding — Hydrostatic water-blocking filler and low-friction separator wrap
Hydrostatic pressure & water blocking	Radial and longitudinal water-blocking integrity verified per BS 6920 WRAS & KTW Approved EPDM Clean-Water Submersible Pump Standard
Standards	BS 6920 WRAS & KTW Approved EPDM Clean-Water Submersible Pump Standard
Core / conductor construction	Flexible Stranded Copper Conductors (4 Cores) — Class 5 / class 6 copper conductors
Continuous operating temperature	−40…+90 °C (submerged seawater & topside deck service)
Storage & transport temperature	−40…+80 °C on export wooden/steel cable drum
Minimum bending radius	5 × OD
Seawater, hydrolysis & oil resistance	Resistant to permanent seawater immersion, hydrolysis, hydraulic oil and bio-fouling per BS 6920 WRAS & KTW Approved EPDM Clean-Water Submersible Pump Standard
RoHS & REACH compliance	RoHS 2 (2011/65/EU + 2015/863) & REACH SVHC compliant

Sizes

3 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Order designation	Configuration	Core / stranding	Outer Ø ≈ mm	Net weight ≈ kg/km	Max. pulling kN ≈	Min. bend R mm
WRAS/KTW EPDM Pump Cable Construction Schedule (−40…+90 °C) 3 sizes						
☐ **WRAS 4G4.0 mm²**	**4G4.0 mm² (3×4.0 + 1G4.0 / 12 AWG)**	**IEC 60228 Class 5 Cu/SnCu**	**14.2**	**340**	**3.2**	**85**
☐ **WRAS 4G16 mm²**	**4G16 mm² (3×16 + 1G16 / 6 AWG)**	**IEC 60228 Class 5 Cu/SnCu**	**21.4**	**840**	**9.6**	**130**
☐ **WRAS 3×50+1G25 mm²**	**3 × 50 + 1G25 mm² (or 3×70+1G35)**	**IEC 60228 Class 5 Cu/SnCu**	**32.8**	**2,240**	**26.5**	**195**

– Custom core counts, optical fiber channels, wet-mate terminations and continuous winch lengths available per BS 6920 WRAS & KTW Approved EPDM Clean-Water Submersible Pump Standard.

Electrical, optical & thermal parameters

3 sizes

Configuration	Max. DC R_{20} Ω/km	Rating / Impedance / Load	Operating temp.
4G4.0 mm² (3×4.0 + 1G4.0 / 12 AWG)	**4.95**	**450/750 V (0.6/1 kV) (36 A Submersible)**	**−40…+90 °C**
4G16 mm² (3×16 + 1G16 / 6 AWG)	**1.21**	**450/750 V (0.6/1 kV) (98 A Submersible)**	**−40…+90 °C**
3 × 50 + 1G25 mm² (or 3×70+1G35)	**0.39**	**450/750 V (0.6/1 kV) (195 A Feeder)**	**−40…+90 °C**

– Every production length undergoes routine conductor DC resistance / OTDR optical attenuation, AC dielectric and dimensional verification.

Standards and approvals

- BS 6920 WRAS / KTW / EN 50525 Compliant
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/wras-ktw-clean-water-epdm-submersible-pump-cable

Typical values for this cable type, based on BS 6920 WRAS & KTW Approved EPDM Clean-Water Submersible Pump Standard. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.