subsea ROV umbilical, AUV tether & sonar tow cable

Wet-Mate Rolling-Seal Optical Cable

Wet-Mate Rolling Seal Optical Wet-Mate Cable

ISO 13628-6 / API 17F · 1,000 V · Subsea rov umbilical, auv tether & sonar tow cable



ISO 13628-6 / API 17F | 1,000 V (-20 to +70 °C) | Subsea / Marine Outer Protective She

Application

Wet-Mate Rolling Seal Optical Wet-Mate Cable featuring single-mode / multi-mode optical unit and subsea / marine outer protective sheath (ISO 13628-6 / API 17F, 1,000 V, -20 to +70 °C, min. bend radius 8 × OD).

Typical uses: Work-Class & Observation ROV Umbilicals and TMS Tethers, Offshore Aquaculture Net Cleaners & Subsea Cage Inspection, AUV, Ocean Glider & Expendable Spool-Payoff Micro-Tethers, USV Towed Sonar Arrays, Seabed Crawlers & Subsea Trenchers

Construction





Cross-section, not to scale

1. Single-Mode / Multi-Mode Optical Unit
2. Power & Control Copper Conductors
3. Subsea / Marine Outer Protective Sheath

Technical data

Typical values

Rated voltage / operating system	1,000 V (ISO 13628-6 & API 17F Rolling-Seal Optical-Electrical Wet-Mate Cable Standard)	**Core / conductor construction**	Single-Mode / Multi-Mode Optical Unit — Hermetic stainless-steel tube / tight-buffered optical unit
Primary dielectric / optical buffer	Power & Control Copper Conductors — Stranded copper conductors with High-density polyethylene (HDPE / PE) core insulation	**Continuous operating temperature**	−20…+70 °C (submerged seawater & topside deck service)
Hydrostatic & thermal cycling endurance	Verified cold-bend and wet dielectric stability across −20…+70 °C per ISO 13628-6 & API 17F Rolling-Seal Optical-Electrical Wet-Mate Cable Standard	**Storage & transport temperature**	−40…+80 °C on export wooden/steel cable drum
Outer jacket / sheath protection	Subsea / Marine Outer Protective Sheath — Black hydrolysis- & abrasion-resistant marine Polyurethane (PUR) outer sheath	**Minimum bending radius**	8 × OD
Reinforcement / screen / bedding layer	Power & Control Copper Conductors — Stranded copper conductors with High-density polyethylene (HDPE / PE) core insulation	**Seawater, hydrolysis & oil resistance**	Resistant to permanent seawater immersion, hydrolysis, hydraulic oil and bio-fouling per ISO 13628-6 & API 17F Rolling-Seal Optical-Electrical Wet-Mate Cable Standard
Hydrostatic pressure & water blocking	Radial and longitudinal water-blocking integrity verified per ISO 13628-6 & API 17F Rolling-Seal Optical-Electrical Wet-Mate Cable Standard	**RoHS & REACH compliance**	RoHS 2 (2011/65/EU + 2015/863) & REACH SVHC compliant
Standards	ISO 13628-6 & API 17F Rolling-Seal Optical-Electrical Wet-Mate Cable Standard		

Sizes

3 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Order designation	Configuration	Core / stranding	Outer Ø ≈ mm	Net weight ≈ kg/km	Max. pulling kN ≈	Min. bend R mm
Wet-Mate Rolling-Seal Optical Cable Construction Schedule (−20…+70 °C) 3 sizes						
☐ **Wet-Mate Rolling-Seal Optical Cable Hybrid 4G2.5**	**4G2.5 mm² Power + 4×SM + 2×2×0.5**	**Class 5 SnCu + Aramid Braid + Subsea PUR**	**14.6**	**285**	**18.0**	**90**
☐ **Wet-Mate Rolling-Seal Optical Cable Hybrid 4G6+F**	**4G6.0 mm² Power + 4×SM/MM + 4×2×0.5**	**Class 5 SnCu + Aramid Braid + Subsea PUR**	**19.2**	**540**	**32.0**	**120**
☐ **Wet-Mate Rolling-Seal Optical Cable Hybrid 4G16+**	**4G16 mm² Power + 8×SM/MM + 4×2×0.75**	**Class 5 SnCu + Heavy Aramid + Subsea PUR**	**26.5**	**1,120**	**55.0**	**165**

– Custom core counts, optical fiber channels, wet-mate terminations and continuous winch lengths available per ISO 13628-6 & API 17F Rolling-Seal Optical-Electrical Wet-Mate Cable Standard.

Electrical, optical & thermal parameters

3 sizes

Configuration	Max. DC R_{20} Ω/km	Rating / Impedance / Load	Operating temp.
4G2.5 mm² Power + 4×SM + 2×2×0.5	**7.98**	**1,000 V · 18 kN Tensile**	**−20…+70 °C**
4G6.0 mm² Power + 4×SM/MM + 4×2×0.5	**3.30**	**1,000 V · 32 kN Tensile**	**−20…+70 °C**
4G16 mm² Power + 8×SM/MM + 4×2×0.75	**1.21**	**1,000 V · 55 kN Tensile**	**−20…+70 °C**

– Every production length undergoes routine conductor DC resistance / OTDR optical attenuation, AC dielectric and dimensional verification.

Standards and approvals

- ISO 13628-6 / API 17F Compliant
- EN 10204 3.1 Factory Test Certificate
- CE, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone
+86 185 9591 3361

Email
info@tebaoflex.com

Web
tebaoflex.com/cables/wet-mate-rolling-seal-optical-wet-mate-cable

Typical values for this cable type, based on ISO 13628-6 & API 17F Rolling-Seal Optical-Electrical Wet-Mate Cable Standard. Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.