Fire-resistant & circuit-integrity cables

XAI(i) 331 150/250V IEC 60092-376 Fire-Resistant

IEC 60092-376 / IEC 60331 Fire Resistant · 150/250 V · -25°C to +90°C · Min. bend 10 × OD




IEC 60092-376 / IEC 60331 Fire Resistant | 150/250 V

Application

XAI(i) 331 150/250V IEC 60092-376 Fire-Resistant manufactured to IEC 60092-376 / IEC 60331 Fire Resistant, rated 150/250 (300) V and -25°C to +90°C with a 10 × OD minimum bending radius for oil, gas & petrochemical installations.

Typical uses: Power distribution & utility networks, Railways, tunnels & public infrastructure, Process instrumentation & oil/gas skids, Industrial automation & control cabinets, Renewable energy, marine & heavy industry

Construction





Cross-section, not to scale

1	Conductor	4P×0.75 mm² Flexible Plain Cu
2	Insulation & Core Identification	Mica glass fire barrier + XLPE insulation (0.75 mm², Black & Light-Blue)
3	Screen / Bedding / Armour Layer	Fibreglass fire-resistant binder tape + Plain Copper Wire Braid Armour (XAI(i) 331)
4	Outer Protective Sheath	Blue SHF1 halogen-free intrinsically-safe / fire-resistant outer sheath

Technical data

Typical values

Nominal / reference voltage	150/250 (300) V	Conductor & core insulation	4P×0.75 mm² Flexible Plain Cu · Mica glass fire barrier + XLPE insulation (0.75 mm², Black & Light-Blue)
Routine dielectric / continuity test	100% factory drum spark & continuity verified	Operating temperature range	-25°C to +90°C
Short-circuit / peak thermal limit	+160 °C to +250 °C (5 s conductor thermal limit)	Flame & fire performance	IEC 60092-376 / IEC 60331 Fire Resistant
Minimum bending radius	10 × OD	Screening / armour architecture	Fibreglass fire-resistant binder tape + Plain Copper Wire Braid Armour (XAI(i) 331)
Outer sheath material & colour	Blue SHF1 halogen-free intrinsically-safe / fire-resistant outer sheath	Standards	IEC 60092-376 / IEC 60331 Fire Resistant

Sizes

3 standard constructions

Tick the sizes you need and send this page to info@tebaoflex.com or WhatsApp +86 185 9591 3361.

Part designation	Configuration	Conductor & shield	Insulation / wall	Outer sheath	Outer diameter mm	Min. bend radius mm	Max. conductor resistance @ 20 °C Ω/km	Copper weight kg/km	Cable weight kg/km	Key electrical / optical rating
XAI(i) 331 150/250V IEC 60092-376 Fire-Resistant 3 sizes										
☐ XAI(i) 331 150/250V IEC 60092-376 Fire-Resistant (4P×0.75 mm²)	4P×0.75 mm²	Class 5 Flexible Plain Copper	Mica glass fire barrier + XLPE insulation	LSZH Jacket	16.5	165	24.13	332.8	640	4 A
☐ XAI(i) 331 150/250V IEC 60092-376 Fire-Resistant (8P×0.75 mm²)	8P×0.75 mm²	Class 5 Flexible Plain Copper	Mica glass fire barrier + XLPE insulation	LSZH Jacket	19.5	195	24.13	463.3	891	4 A
☐ XAI(i) 331 150/250V IEC 60092-376 Fire-Resistant (12P×0.75 mm²)	12P×0.75 mm²	Class 5 Flexible Plain Copper	Mica glass fire barrier + XLPE insulation	LSZH Jacket	22.8	228	24.13	633.4	1,218	4 A

– Dimensions and weights are nominal manufacturing targets subject to standard production tolerances.

Standards and approvals

- ✓ IEC 60092-376 / IEC 60331 Fire Resistant Compliant
- ✓ EN 10204 3.1 Factory Test Certificate
- ✓ CE, UKCA, RoHS 2 (2011/65/EU) & REACH

Certifications

Management systems: ISO 9001, ISO 14001, ISO 45001

Request a quotation

Send the size, length and destination. An application engineer replies within 2 business hours.

WhatsApp / phone **+86 185 9591 3361**

Email **info@tebaoflex.com**

Web **tebaoflex.com/cables/xai-i-331-150-250v-iec-60092-376-fire-resistant**

Typical values for this cable type, based on Reference specification per IEC 60092-376 / IEC 60331 Fire Resistant (XAI(i) 331 150/250V IEC 60092-376 Fire-Resistant). Values for your order are confirmed in the quotation. Subject to change without notice. Jiangsu Tebaoflex Special Cable Co., Ltd., Taicang, Jiangsu, China.